

ROLL-X® Multipurpose Applicator 327 / 175 ADVANTAGE



KEY FEATURES

- Manual height adjustment 850-1 070mm / 2ft. 9in. – 3ft. 6in.
- Adjustable side trays
- Metal side lines used for trimming
- Fast assembly and installation

ROLL-X Advantage gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! Possible to retrofit LED and Electrical height adjustable legs.



| MODEL NAME | ROLL-X® 327/175 Advantage |
|--|---|
| Model type | Advantage |
| Part no. | 10529 |
| Bed length | 3 270 mm / 10ft. 9in. |
| Bed width | 1 750 mm / 5ft. 9in. |
| Length of working area | 2 870 mm / 9ft. 5in. |
| Width of working area/roller width | 1 650 mm / 5ft. 5in. |
| Overall width incl. Glide beam | 1 940 mm / 6ft. 4in. |
| Max. thickness of substrate | 85 mm / 3 2/5in. |
| Work height flatbed | 850-1 070mm / 2ft. 9in – 3ft. 6in. |
| Bed surface | Tempered glass + Cutting mat |
| Power Supply | 230V/50Hz (10A) / 120V/60Hz 15A) |
| Required air pressure | 6-8 bar / 87-116 psi |
| Weight | 560 kg / 1 235 lb |
| Packing weight, total | 760 kg / 1 676 lb |
| Packing dimension, delivered in parts | 3 500 x 710 x 2 100 mm / 11ft 6in. x 2ft. 4in. x 6ft. 10in. |
| Packing dimension, delivered assembled | 3 500 x 2 000 x 1 600 mm / 11ft 6 in. x 6ft 7in. x 5ft 3in. |
| Wheels | 4 |
| Warranty | 2 years |
| Owner's Manual | yes (en) |
| Roll holder for Glide Beam | yes |
| Roll holder for bed end | yes |
| Side trays, adjustable | Yes |
| Roll cradle, 1300mm / 4ft 3in. | option |
| Light table (LED) | option |
| Electrical height adjustment | option |
| Long life compressor | option |
| Assembled at delivery | option |

ROLL-X
MULTIPURPOSE APPLICATOR

info@roll-x.se
roll-x.se
+46 54 770 70 00