

ROLL-X® Multipurpose Applicator 470/175 ADVANTAGE



KEY FEATURES

- Manual height adjustment 850-1 070mm / 2ft. 9in. – 3ft. 6in.
- Adjustable side trays
- Metal side lines used for trimming
- Fast assembly and installation

ROLL-X Advantage gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! Possible to retrofit LED and Electrical height adjustable legs.



MODEL NAME	ROLL-X® 470/175 Advantage
Model type	Advantage
Part no.	10533
Bed length	4 700 mm / 15ft. 5in.
Bed width	1 750 mm / 5ft. 9in.
Length of working area	4 300 mm / 14ft. 1in.
Width of working area/roller width	1 650 mm / 5ft. 5in.
Overall width incl. Glide beam	1 940 mm / 6ft. 4in.
Max. thickness of substrate	85 mm / 3 2/5in.
Work height flatbed	850-1 070mm / 2ft. 9in – 3ft. 6in.
Bed surface	Tempered glass + Cutting mat
Power Supply	230V/50Hz (10A) / 120V/60Hz 15A)
Required air pressure	6-8 bar / 87-116 psi
Weight	740 kg / 1 631 lb
Packing weight, total	1 040 kg / 2 293 lb
Packing dimension, delivered in parts	4 800 x 710 x 1 800 mm / 15ft 9in. x 2ft. 4in. x 5ft. 10in.
Packing dimension, delivered assembled	4 800 x 2 000 x 1 600 mm / 15ft 9in. x 6ft 7in. x 5ft 3in.
Wheels	4
Warranty	2 years
Owner's Manual	yes (en)
Roll holder for Glide Beam	yes
Roll holder for bed end	yes
Side trays, adjustable	yes
Roll cradle, 1300mm / 4ft 3in.	option
Light table (LED)	option
Electrical height adjustment	option
Long life compressor	option
Assembled when delivered	option

ROLL-X
MULTIPURPOSE APPLICATOR

info@roll-x.se
roll-x.se
+46 54 770 70 00